

signal

JOFRA™

Input and Output

Current: 0 to 24 mA
Voltage: 0 to 200 mVDC
0 to 20 VDC (source)
0 to 28 VDC (read)

High level of protection

Fuse-less protection for internal circuitry
- a common cause of failure in other units
without this protection

Auto-stepping

Auto-step feature for simulation or sourcing
for easy performance of repeated test or
validation steps

Easy to use

User-friendly controls with knob and
keypad allow for function specific
operations and adjustable values

High accuracy

Accuracy up to $\pm 0.015\%$ of reading ± 2
units - with ranges including mA, mV, and
VDC

Large display

Including large numbers for unit reading, a
percentage display, and dedicated icons
for calibrator status

HART resistor

Built-in 250 resistor for HART device
communications - place for resistor in
circuit as needed

Complete marine program

Part of a complete program of marine
approved temperature, pressure and signal
calibrators; including temperature sensors

ISO 9001 Manufacturer

INSTRUMENTS • CONTROLS • VALVES

ARCO
Engineering, Inc.
SINCE 1954
www.arcoengineering.com

3317 Gilmore Industrial Blvd.
Louisville, KY 40213

Ph: (502) 966-3134
Fx: (502) 966-3135

Specification Sheet
SS-CP-2330-US

Model CSC100

Compact Signal Calibrator

PRODUCT DESCRIPTION

The JOFRA CSC100 is your solution to loop calibration. This handheld calibrator offers you an easy to operate interface including a knob for precise and rapid adjustment. With features including a large display and an auto stepping signal, the CSC100 makes troubleshooting and calibration of your process equipment a snap.



Features

The CSC line of signal calibrators are dedicated units designed to make your calibration and maintenance tasks easier to perform. The JOFRA CSC100 is engineered for instrument loop calibrations and is specifically manufactured for 4 to 20 mA loops; however this versatile instrument offers much more than than.

This calibrator can source and read current and voltage; including millivolts. It can also be used as a signal simulator to test your transmitters without the need for actual operation.

The CSC100 also offers features such as an auto-stepping function and fuse-less protection. These handy time savers are combined in a package offering an easy-to-read, two line display, and an intuitive keypad with a knob for fine adjustments.

This calibrator is more than a simple tool but it is as straightforward as any device that you have in the toolbox. The CSC100 signal calibrator offers the accuracy and features needed in a convenient, compact, and easy-to-use package.

AMETEK®
CALIBRATION INSTRUMENTS

Clear dual line display

The CSC100 features a large two-line display. The upper line shows the measured or sourced voltage or current value. The second line is available in the mA modes to show the percentage of 4 to 20 mA. The display also features several icons to allow for quick recognition of the status of the unit.

Electrical connections

Inputs for current and voltage measurement and sourcing.

V/mA

Selects between the voltage and current functions.

ON / OFF

Auto shut-off to extend battery life (user programmable).

LOOP PWR

Turns on 24 VDC loop power when the calibrator is in the mA measure mode. Icon on the display indicates when this mode is active.

Left / Right arrows

Move the cursor left or right to allow for adjustment of the desired decade.

Mode

Select the input or output mode.

25%

Steps the output in mA source or simulate mode in increments of 25% (4 mA).

AUTO

Enables automatic step functions. Perform tests using stored test points. Icon on display indicates when this mode is active. User can select between fast or slow ramping.

Adjustment knob

Allows for easy adjustment of values. Combined with the Arrow Keys, reaching the desired value is easy.



Overview

The CSC100 is a signal loop calibrator; it is designed to source and read voltage and current for loop signal calibration. This unit is a handy calibrator that can meet applications such as simulating a transmitter in a loop, measuring voltage, and checking output mA or mV levels.

The CSC100 is not simply a calibrator but an effective troubleshooting and test device. This versatile instrument is dedicated to loop calibration but that does not mean that this instrument is made to do only one thing.

Voltage modes

The CSC100 offers the ability to source and read voltage. There is a VDC and mVDC scale to meet multiple applications. This allows the unit to function as a source to indicators and to other functions that are driven by voltage signals. The CSC100 can be used to drive a meter to specific setpoints for validation of operation without the need for other equipment. It is also possible to take a quick voltage measurement.

Current modes

The CSC100 offers four different functions in the current mode. It can source current to inject a signal into a loop or simulate current and it may act as the transmitter in the loop to drive other functions or remote indications. The unit can simply be used to measure current. Additionally the CSC100 can power and read the instrument at the same time; providing that the unit under test is removed from the loop while under test or is removed from the system.

Setpoint operation

The CSC100 offers a one button feature that is missing on many other loop calibrators. When it is sourcing or simulating current, the 25% key can be used to step in increments through a test or calibration. The calibrator will output mA values corresponding to 25% steps for a 4 to 20 mA transmitter. Just connect the unit and set it for current simulation or sourcing and press the key, the value will be 8 mA or 25%. Then, continue to use the function to step up through to 100% of the reading. It is possible to have the manual control of the test, but the calibrator takes care of the calculation for your test points.

Automatic operation

In addition to the manual stepping with the 25% key, the CSC100 takes functionality one step further and offers an automatic option. This is again a one button solution utilizing the AUTO key. Set the unit up to simulate or source current and then press the AUTO key. This will activate the auto stepping feature and the calibrator will step through 25, 50, 75, and 100% values for a 4 to 20 mA device. These steps occur once every 5 seconds. If a faster test is needed the AUTO key may be pressed again to activate fast ramping.

Auto shutdown

The CSC100 offers an automatic shutdown feature. This power saving feature turns the calibrator off after it has been idle for a specified period of time. The time delay is factory set to 30 minutes, however the time may be adjusted.

CSC100 in soft case

All JOFRA handheld calibrators are supplied in a handy soft case that allows for operation while in the case. The convenient internal storage pocket offers the space for test leads and accessories.



FUNCTIONAL SPECIFICATIONS

Ranges

mA input/output 0 to 24 mA / -25 to 125 %
mV input/output 0 to 200 mV
Volts input 0 to 28 V
Volts output 0 to 20 V
Max load 1000 Ω
Max load w/HART resistor: 750 Ω

Accuracy1

mA ±0.015% of reading ±2 μA
mV ±0.02% of reading ±20 μV
Volts ±0.015% of reading ±2 mV

1) Specification at 23°C ±5°C / 73.4°F ±9°F including non-linearity, hysteresis, and repeatability.

Display

LCD Dual line plus icons
Display resolution 5 digits
Display update 4 times per second

Temperature range

Operating -10 to 50°C / 14 to 122°F
Storage -20 to 60°C / -4 to 140°F

Power supply

Battery 1 x 9 V Alkaline
Battery life Minimum 20 hours
Low battery indicator at 7 V

Instrument dimensions

Indicator L x W x H .. 188 x 84 x 52 mm / 7.4 x 3.3 x 2.1 in
Indicator weight (including battery) 400 g / 14.1 oz
Indicator L x W x H, shipping 203 x 101 x 64 mm / 8.0 x 4.0 x 2.5 in
Indicator weight (including battery) 567 g / 20 oz

ORDERING INFORMATION

Order no.	Description
CSC100	Handheld loop signal calibrator
Certification	
G	NIST traceable temperature certificate (standard)
H	Accredited calibration certificate
CSC100G	Sample order number
CSC100 calibrator with standard NIST traceable temperature certificate	

STANDARD DELIVERY

- JOFRA CSC100 loop calibrator
- Traceable calibration certificate
- Reference manual
- Test leads
- Soft carrying case
- Shoulder strap

ACCESSORIES

- 124717 1x 9 Volt rechargeable battery
- 124718 Charger for rechargeable batteries - 115/230 VAC



AMETEK Calibration Instruments is one of the world's leading manufacturers and developers of calibration instruments for temperature, pressure and process signals as well as for temperature sensors both from a commercial and a technological point of view.

JOFRA Temperature Instruments
Portable precision thermometers. Dry-block and liquid bath calibrators: 4 series, with more than 25 models and temperature ranges from -90° to 1205°C / -130° to 2200°F. All featuring speed, portability, accuracy and advanced documenting functions with JOFRACAL calibration software.

JOFRA Pressure Instruments
Convenient electronic systems ranging from -1 to 1000 bar (25 inHg to 14,500 psi) - multiple choices of pressure ranges, pumps and accuracies, fully temperature-compensated for problem-free and accurate field use.

JOFRA Signal Instruments
Process signal measurement and simulation for easy control loop calibration and measurement tasks - from handheld field instruments to laboratory reference level bench top instruments.

JOFRA / JF Marine Instruments
A complete range of calibration equipment for temperature, pressure and signal, approved for marine use.

FP Temperature Sensors
A complete range of temperature sensors for industrial and marine use.

M&G Pressure Testers
Pneumatic floating-ball or hydraulic piston dead weight testers with accuracies to 0.015% of reading.

M&G Pumps
Pressure generators from small pneumatic "bicycle" style pumps to hydraulic pumps generating up to 1,000 bar (15,000 psi).

*...because calibration is
a matter of confidence*

AMETEK[®]
CALIBRATION INSTRUMENTS

Headquarters:

AMETEK Denmark A/S
Gydevang 32-34 • 3450 Allerød • Denmark
Tel: +45 4816 8000 • ametek@ametek.dk

Sales & Service:
Europe, Asia, Africa, Middle East and South America

Information in this document is subject to change without notice.
©2008, by AMETEK, Inc., www.ametek.com. All rights reserved.

Pub code SS-CP-2330-US Issue 0901

www.ametekcalibration.com
www.jofra.com

Sales & Service Offices:

AMETEK Mansfield & Green (North America)
Tel: +1 800 527 9999 • cal.info@ametek.com

AMETEK Singapore Pte. Ltd. (Singapore)
Tel: +65 6 484 2388 • aspl@ametek.com.sg

AMETEK Inc. Beijing Rep. Office (China)
Tel: +86 10 8526 2111 • jofra@ametek.com.cn

AMETEK GmbH (Germany)
Tel: +49 2159 9136 510 • info.mct-de@ametek.de

AMETEK Calibration Instruments (UK)
Tel: +44 (0) 1489 486 404 • jofra@ametek.co.uk