



Since 1954

3317 Gilmore Industrial Blvd
Louisville, KY 40213
(502) 966-3134

www.ArcoEngineering.com
Sales@ArcoEngineering.com

Temperature Switch Datasheet United Electric Controls

p/n: F120-6BS

FACTORY DIRECT - AUTHORIZED DISTRIBUTOR
Contact us for: [Application Assistance](#), [Quotes](#), to [Place an Order](#)

UE PART NUMBER: F120-6BS

ENCLOSURE: Class I, Division 1 and 2, Groups B, C & D
Class II, Division 1 and 2, Groups E, F & G
Class III
Enclosure Type 4X

¹ SWITCH: Single SPDT 15A 125,250,480 VAC Resistive

ELECTRICAL CONNECTION: 3/4" NPT Female

SET POINT ADJUSTMENT METHOD: Internal

WETTED AND SENSOR TYPE: 304SS Plain Capillary with 304SS Remote Bulb

SENSOR: 3/8" O.D. x 4-1/2" Length Bulb, 6Ft. Capillary

ADJUSTABLE SET POINT RANGE: 0 to (+)250 F

² MAXIMUM TEMPERATURE: 300 F

COMPLETE SPECIFICATIONS & OPTIONS: [United Electric 120 Series Product Catalog](#)

¹ See United Electric Controls catalog for further rating details and optional microswitches.

² Maximum Temperature: The maximum temperature to which a sensor may be occasionally subjected, which causes no permanent damage. The unit may require calibration.