



Since 1954

3317 Gilmore Industrial Blvd
Louisville, KY 40213
(502) 966-3134

www.ArcoEngineering.com
Sales@ArcoEngineering.com



Differential Pressure Switch Datasheet

United Electric Controls

p/n: H100K-548

FACTORY DIRECT - AUTHORIZED DISTRIBUTOR

Contact us for: Application Assistance, Quotes, to [Place an Order](#)

UE PART NUMBER:	H100K-548
ENCLOSURE:	Epoxy Powder Coated Die Cast Aluminum Captive Cover Screws Enclosure Type 4X
¹ SWITCH:	Single SPDT 15A 125,250,480 VAC Resistive
ELECTRICAL CONNECTION:	1/2" NPT Female
PRESSURE CONNECTION:	1/8" NPT Female
PRESSURE CONNECTION MATERIAL:	Epoxy Coated Aluminum
SENSOR:	Buna-N® Diaphragm
² ADJUSTABLE SET POINT RANGE:	100 to 500 PSID
³ PROOF PRESSURE:	2500 PSI
COMPLETE SPECIFICATIONS & OPTIONS:	United Electric 100 Series Product Catalog
¹ See United Electric Controls catalog for further rating details and optional microswitches.	
² Low end of range on fall; High end of range on rise.	
³ Proof Pressure: The maximum pressure to which a pressure sensor may be occasionally subjected, which causes no permanent damage. The unit may require calibration.	

The information in this document is subject to change without notice and should not be construed as a commitment by ARCO Engineering, Inc. ARCO Engineering, Inc. assumes no responsibility for any errors that may appear on this document. In no event shall ARCO Engineering, Inc. be liable for incidental or consequential damages arising from use of the information described herein.