




Since 1954

3317 Gilmore Industrial Blvd
Louisville, KY 40213
(502) 966-3134

www.ArcoEngineering.com
Sales@ArcoEngineering.com



Pressure Switch Datasheet
United Electric Controls
p/n: H117K-541

FACTORY DIRECT - AUTHORIZED DISTRIBUTOR
Contact us for: Application Assistance, Quotes, to Place an Order

UE PART NUMBER:	H117K-541
ENCLOSURE:	Class I, Division 2, Groups A, B, C & D Class II, Division 2, Groups F & G Class III Enclosure Type 4X
¹ SWITCH:	Single SPDT 11A 125,250 VAC Resistive, Hermetically Sealed
ELECTRICAL CONNECTION:	1/2" NPT Female
PRESSURE CONNECTION:	1/8" NPT Female
PRESSURE CONNECTION MATERIAL:	Epoxy Coated Aluminum
SENSOR:	Buna-N [®] Diaphragm
² ADJUSTABLE SET POINT RANGE:	2 to 20 "H2O Differential
³ PROOF PRESSURE:	400 PSI
COMPLETE SPECIFICATIONS & OPTIONS:	United Electric 117 Series Product Catalog
¹ See United Electric Controls catalog for further rating details and optional microswitches.	
² Low end of range on fall; High end of range on rise.	
³ Proof Pressure: The maximum pressure to which a pressure sensor may be occasionally subjected, which causes no permanent damage. The unit may require calibration.	

The information in this document is subject to change without notice and should not be construed as a commitment by ARCO Engineering, Inc. ARCO Engineering, Inc. assumes no responsibility for any errors that may appear on this document. In no event shall ARCO Engineering, Inc. be liable for incidental or consequential damages arising from use of the information described herein.