




Since 1954

3317 Gilmore Industrial Blvd
Louisville, KY 40213
(502) 966-3134

www.ArcoEngineering.com
Sales@ArcoEngineering.com



Pressure Switch Datasheet
United Electric Controls
p/n: H122-452

FACTORY DIRECT - AUTHORIZED DISTRIBUTOR
Contact us for: Application Assistance, Quotes, to [Place an Order](#)

UE PART NUMBER:	H122-452
ENCLOSURE:	Class I, Division 1 and 2, Groups B, C & D Class II, Division 1 and 2, Groups E, F & G Class III Enclosure Type 4X
¹ SWITCH:	Dual SPDT 15A 125,250,480 VAC Resistive
ELECTRICAL CONNECTION:	3/4" NPT Female
PRESSURE CONNECTION:	1/4" NPT Female
PRESSURE CONNECTION MATERIAL:	Stainless Steel
SENSOR:	Buna-N [®] Diaphragm
² ADJUSTABLE SET POINT RANGE:	30" Hg Vac to 20 PSI
³ PROOF PRESSURE:	225 PSI
COMPLETE SPECIFICATIONS & OPTIONS:	United Electric 120 Series Product Catalog
¹ See United Electric Controls catalog for further rating details and optional microswitches.	
² Low end of range on fall; High end of range on rise.	
³ Proof Pressure: The maximum pressure to which a pressure sensor may be occasionally subjected, which causes no permanent damage. The unit may require calibration.	

The information in this document is subject to change without notice and should not be construed as a commitment by ARCO Engineering, Inc. ARCO Engineering, Inc. assumes no responsibility for any errors that may appear on this document. In no event shall ARCO Engineering, Inc. be liable for incidental or consequential damages arising from use of the information described herein.